

WALKOTE

SKIM SMOOTH RENDERING PASTE

PRODUCT DESCRIPTION

Walkote is a specially formulated **water resistant** white cement based putty suitable for plastered and concrete surfaces for both internal and external walls.

Walkote superior formulation is designed to provide a smooth durable finish with excellent adhesion strength. The surface can be either brushed or trowelled finished to meet stringent requirements. **Walkote** yields a homogeneous paste that gives good workability on both vertical and overhead surfaces.

PRODUCT ADVANTAGES

- Premixed to ensure good consistent quality.
- Adjustable consistency & Excellent trowelability on application.
- Due to presence of cement and polymer, it provides a hard and tough surface.
- Being Cementitious it forms an excellent bond with plaster
- Seal all cracks and pores in the concrete
- Can be applied on moist plaster without waiting for drop in moisture. Hence improvement in Project Completion Schedule.
- Perfectly smooth finish.
- Compatible with decorative wall coatings.
- Water resistant and no curing required

METHOD OF APPLICATION

a) SURFACE PREPARATION

The surface must be clean, sound, dust-free, and without any traces of oil, laitance, paint or curing compound.

b) PRODUCT PREPARATION

Add approximately 9-10 litre of water to 25 kg of **Walkote**. Mix thoroughly for 3-5 minutes until the desired homogeneous paste is achieved and ready to use.

c) PRODUCT APPLICATION

Walkote is applied using a steel trowel and will remain workable for approximately 60 minutes after mixing.

STORAGE

Walkote must be stored in a cool dry place and free from moisture contact. **Walkote** has a shelf life of 12 months from the date of manufacture in unopened original container.

HEALTH AND SAFETY

Walkote is non-hazardous. In case of eye contact, wash with plenty of water. If irritation persists, seek immediate medical attention.

PACKAGING

Walkote is supplied in 25 kg bag.